



























Insulated Terminals

ITEM NO.	AWG 12-10 DIN 4-6	STUD SIZE	ITEM	TYPE	RANGE SIZE.
RING TERMINALS			FULL INSULATED		
VF 5.5-4		#8/4.3mm	RF250F		Wire Range 22-16 / TAB 6.4mm
VF 5.5-5		#10/5.3mm	BF250F		Wire Range 16-14 / TAB 6.4mm
VF 5.5-6		#1/4"/6.4mm			
VF 5.5-8		#5/16"/8.4mm			
VF 5.5-10		#3/8"/10.5mm			
FORKED SPADE			PIGGY BACK		
VF 5.5-4Y		#8/4.3mm	MF-1.25		Wire Range 22-16 / TAB 6.4mm
VF 5.5-5Y		#10/5.3mm	MF-2		Wire Range 16-14 / TAB 6.4mm
VF 5.5-6Y		#1/4"/6.4mm	MF5.5		Wire Range 12-10 / TAB 6.4mm
MALE DISCONNECTORS			STRIPPING QUICK SPLICE		
3150A		TAB 2.8mm	878100		
4150A		TAB 4.8mm	878101		
5150A		TAB 6.4mm	878201		
FEMALE DISCONNECTORS					
3150B		TAB 2.8mm			
4150B		TAB 4.8mm			
5150B		TAB 6.4mm			
BULLET DISCONNECTORS					
F5.5A		5mm BULLET			
F5.5B		5mm BULLET			
BUTT DISCONNECTORS					
BF-5.5					
PIN DISCONNECTORS					
PIN-5.5		TAB 2.8mm			